

09-05-00

A

09/01/00

1543 U.S. PTO

Please type a plus sign (+) inside this box → ☐PTO/SB/05 (12/97) (modified)  
Approved for use through 09/30/00 OMB 0651-0032  
Patent and Trademark Office U.S. DEPARTMENT OF COMMERCEUTILITY  
PATENT APPLICATION  
TRANSMITTAL

Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

TB3/TL

Total Pages

101

First Named Inventor or Application Identifier

Clarence Red Martinet al.

Express Mail Label No.

EL 584 933 348 US

1543 U.S. PTO  
09/01/00

09/01/00

## CERTIFICATE OF MAILING BY "EXPRESS MAIL"

Express Mail Label No.: EL 584933348US

Date of Deposit: 9/1/00

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231.

*for*

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

1. ☒ Fee Transmittal Form  
(Submit an original, and a duplicate for fee processing)
  2. ☒ Specification [Total Pages (including)
    - Descriptive title of the invention
    - Background of the invention
    - Brief Summary of the invention
    - Brief Description of the Drawings (if filed)
    - Detailed Description
    - Claim(s)
    - Abstract of the Disclosure
  3. ☒ Drawing(s) (35 USC 113) [Total Sheets   - 4. ☒ Oath or Declaration [Total Pages   - a. ☒ Newly executed (original or copy)
  - b. ☐ Copy from a prior application (37 CFR 1.63(d)  
(for continuation/divisional with Box 17 completed)  
[Note Box 5 below]
  - i. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting inventor(s) named in  
the prior application, see 37 CFR 1.63(d)(2) and 1.33(b)
5. ☐ Incorporation By Reference (useable if Box 4b is checked)  
The entire disclosure of the prior application, from which a copy of the  
oath or declaration is supplied under Box 4b, is considered as being  
part of the disclosure of the accompanying application and is hereby  
incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission  
(if applicable, all necessary)
  - a. Computer Readable Copy
  - b. Paper Copy (identical to computer copy)
  - c. Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney  
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)
14. ☒ Small Entity ☐ Statement filed in prior application,  
Statement(s) Status still proper and desired
15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) ☒ Provisional of prior application No: 60/157,904 filed October 5, 1999

## 18. CORRESPONDENCE ADDRESS

Customer No. 23844  
 Scott C. Harris  
 Registration No. 32,030  
 P.O. Box 927649  
 San Diego, CA 92192  
 Telephone: (619) 823-7778  
 Facsimile: (877) 690-9638

The filing fee has been calculated as follows:

FOR	NUMBER FILED	NUMBER EXTRA	RATE	CALCULATIONS
TOTAL CLAIMS	179 - 20 =	159	x \$9.00	\$1,431
INDEPENDENT CLAIMS	20 - 3 =	17	x \$39.00	\$ 663
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$260.00	\$0
			BASIC FEE	\$345.00
			TOTAL OF ABOVE CALCULATIONS =	\$2,439
Assignment Recording Fee (if enclosed)				\$40.00
			TOTAL =	\$2,479

☒ A check in the amount of \$2,479.00 is attached.

☐ Charge \$\_\_\_\_\_ to **Deposit Account No.**\_\_\_\_\_ referencing docket no. \_\_\_\_\_.

Applicant(s) hereby petitions for any required relief including extensions of time and authorizes the Commissioner to charge the cost of such petitions and/or other fees or to credit any overpayment to **Deposit Account No. 50-1387** referencing docket no. **TB3/TL**. A duplicate copy of this transmittal is enclosed, for that purpose.

Dated: 9/1/00

Respectfully submitted,

By: Scott C. Harris  
 Scott C. Harris  
 Registration No. 32,030

Customer No. 23844  
 Scott C. Harris  
 P.O. Box 927649  
 San Diego, CA 92192  
 Telephone: (619) 823-7778  
 Facsimile: (877) 690-9836

ATTORNEY DOCKET NO. TB3/TL/SCH

Applicant or Patentee: Darryl Costin et al.  
 Serial or Patent No.: \_\_\_\_\_  
 Filed or Issued: Herewith  
 For: MATERIAL SURFACE PROCESSING WITH A LASER THAT HAS A SCAN MODULATED  
EFFECTIVE POWER TO ACHIEVE MULTIPLE WORN LOOKS

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS**  
 (37 CFR 1.9(f) and 1.27(e)) — SMALL BUSINESS CONCERN

I hereby declare that I am

- ☐ the owner of the small business concern identified below:  
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

Name of Small Business Concern: Technolines, LLC  
 Address of Small Business Concern: Toledo, Ohio

I hereby declare that the above identified small business concern qualifies as a small business concern as defined in 13 CFR 121.12, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees to the United States Patent and Trademark Office, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled MATERIAL SURFACE PROCESSING WITH A LASER THAT HAS A SCAN MODULATED EFFECTIVE POWER TO ACHIEVE MULTIPLE WORN LOOKS by inventor(s) Darryl Costin and Clarence Martin described in:

- ☒ the specification filed herewith.  
☐ application serial no. \_\_\_\_\_, filed \_\_\_\_\_  
☐ patent no. \_\_\_\_\_, issued \_\_\_\_\_

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below\* and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(e) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e). \*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

Full Name: Technolines, LLC  
 Address: 405 Madison Avenue, 20th Floor, Toledo, Ohio  
☐ INDIVIDUAL ☒ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status when any new rule 53 application is filed or prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent on which this verified statement is directed.

Name:	<u>Tracy Moore</u>
Title:	<u>Manager</u>
Address:	<u>405 Madison Avenue, 20th Floor Toledo, OH 43606</u>

Signature: [Signature] Date: August 16, 2000

APPLICATION  
FOR  
UNITED STATES LETTERS PATENT

TITLE: MATERIAL SURFACE PROCESSING WITH A LASER  
THAT HAS A SCAN MODULATED EFFECTIVE POWER  
TO ACHIEVE MULTIPLE WORN LOOKS

APPLICANT: CLARENCE MARTIN AND DARRYL COSTIN

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EL584933348US

This correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Date of Deposit

9-1-00

Signature

*Clarence Martin*

Typed or Printed Name of Person Signing Certificate

*Clarence Martin*

MATERIAL SURFACE PROCESSING WITH A LASER THAT HAS A SCAN  
MODULATED EFFECTIVE POWER TO ACHIEVE MULTIPLE WORN LOOKS

5

Cross Reference To Related Applications

This application claims the benefit of the U.S. Provisional  
Application No. 60/157,904, filed on October 5, 1999.

10

Background

Denim and other material garments have often been processed  
to make them look worn. Consumers have shown a desire to  
purchase broken-in garments.

15

Currently available techniques of processing such garments  
include mechanical sandblasting with sand or other abrasive;  
hand, mechanical, or robotic rubbing, and others. The effects  
may include local abrasion which is a wear pattern from below  
the waist to below the knee section. Another effect is global  
abrasion, which describes a wear pattern from below the waist to  
the cuff. "Whiskers" are a term which describes the wear that  
occurs along the creases and hem of the article during wear.

20

Yet another worn look is a rectangular area marked on the rear  
pocket of the jean, which simulates the worn look caused from

25

carrying a wallet in the back pocket. Yet another worn look is referred to as "frayed", where the degree of wear is so severe that the individual threads of the cotton fiber are exposed. Such a pattern section may even have holes in the denim fabric.

5       The sandblasting process for local and global abrasion may use sandblasting equipment to abrade the denim jeans with sand particles or other abrasive media. This process blasts sand particles from a sandblasting device to a pair of jeans. The random spatial distribution of the sand creates a special appearance in a treated area that is referred to as "feathered".

10       The abrasion in the feathered area varies from light along the perimeter of the pattern, e.g., the edges and top of the pattern, to heavy in the center of the pattern. This unique appearance may simulate the look of denim jeans that have been worn for a considerable time.

15       However, the sandblast process has a number of problems and limitations. For example, the process of blasting sand or other abrasive media presents environmental and health issues.

Typically, a worker needs to wear protective gear and masks to  
20       reduce the impact of inhaling airborne sand. The job is considered to be a hazardous job, and may cause high employee turnover.

The individual skill of the operator may also be critical in reducing the scrap rate associated with the sandblast process. This has the additional effect of increasing certain costs of labor for the sandblast operator which are typically  
5 higher than the labor rate for other employees in the denim finishing plant, since their skill may be important. The actual blasting process may occur in a room which is shielded from other areas in the manufacturing facility.

Further environmental issues arise with the cleanup and  
10 disposal of the sand.

The sandblasting process is an abrasive process, which causes wear to the sandblasting equipment. Often, the equipment needs to be replaced on a yearly basis or even more frequently.

This, of course, can result in added capital, maintenance and  
15 installation expense.

Also, new designs such as shadow effects along the top or bottom of the whisker are difficult to impossible to obtain with the conventional sandblasting processes.

All in all, the sandblasting process may cost in excess of  
20 \$1.00 per pair of jeans, due to the cost of labor, materials, and scrap produced, and environmental clean up required. It is difficult to duplicate the exact placement of the sandblast

pattern from one garment to the next due to the variability of the process itself and the variability from one laborer to another.

5 The sandblast process can also adversely affect the tear and tensile properties of the denim jeans due to the abrasion of the sand on the denim. It is not uncommon for the sandblast process to reduce the tear and tensile strength of the denim by as much as 50%. Further, the tear and tensile strength variation following sandblasting is high due to the uncontrollability of the abrasive process. Some manufacturers even need to test the tear and tensile properties of the denim at specific locations where the abrasion is the least to even pass the apparel company standards for tear and tensile strength.

15 Other approaches to creating worn looks present their own problems. In the case of whiskers or frayed looks, manufacturers may rely upon very labor intensive, expensive and slow hand rubbing or sanding processes where the whiskers or frayed looks are applied to the denim by hand sanding, sometimes with a rotating drill such as a DREMEL™ tool. In addition to the labor costs associated with such a process, this hand sanding operation is often associated with defects after



washing, where the sanding of the individual whiskers on the denim may be too little or too much resulting in a low quality product. Some manufacturers have even tried to use robotic sanding processes to avoid these problems, albeit at  
5 considerable capital investment and limited flexibility.

Despite the above shortcomings, sandblasting and rubbing processes remain in wide use because the market desires worn look denim.

The present assignee has disclosed laser processing of denim, e.g. in US Patent numbers 5,990,444; 6,002,099 and  
10 5,916,961. These techniques enable using a laser to change the look of a textile product.

#### Summary

15 In recognition of the above, the inventors propose new laser scribing devices and techniques to simulate specified worn looks on fabrics and garments.

One aspect includes using a laser to scribe lines on a garment, where the energy density per unit time of the laser  
20 causes the garment to change color to varying degrees from indigo blue or black to white or grey. Both the individual scanned lines and different sections of a lazed pattern can have

washing, where the sanding of the individual whiskers on the denim may be too little or too much resulting in a low quality product. Some manufacturers have even tried to use robotic sanding processes to avoid these problems, albeit at  
5 considerable capital investment and limited flexibility.

Despite the above shortcomings, sandblasting and rubbing processes remain in wide use because the market desires worn look denim.

The present assignee has disclosed laser processing of denim, e.g. in US Patent numbers 5,990,444; 6,002,099 and  
10 5,916,961. These techniques enable using a laser to change the look of a textile product.

#### Summary

15 In recognition of the above, the inventors propose new laser scribing devices and techniques to simulate specified worn looks on fabrics and garments.

One aspect includes using a laser to scribe lines on a garment, where the energy density per unit time of the laser  
20 causes the garment to change color to varying degrees from indigo blue or black to white or grey. Both the individual scanned lines and different sections of a lazed pattern can have

varied energy density per unit time. The variation in energy density per unit time can be controlled by changing the power, speed, distance, or duty cycle of the laser as the lines are scribed on the material.

5 Other aspects are also disclosed.

Brief Description Of The Drawings

These and other aspects will now be described in detail with respect to the accompanying drawings, wherein:

10 Figure 1 shows an overall lasing system;

Figure 2 shows a controllable laser system;

Figure 3 shows a control screen for a specified worn look;

Figure 4-12 show control screens for different specified worn looks;

15 Figure 13 shows a material delivery system with automatic turnover; and

Figure 14 shows a material delivery system with a dual sided laser.

DETAILED DESCRIPTION

The described system and method teaches a system for producing worn looks on textile materials and/or garments that are made from these textile materials. These worn looks can include abrasion effects which simulate the look of a worn garment, whisker effects, frayed effects, as well as any other effect which is produced on a garment or another product made from a textile material and which makes the textile material look more like a used textile material. In addition, entirely new looks are possible from this invention that cannot be reproduced from the conventional sandblasting or rubbing process. This is done using a number of techniques described in detail herein.

A first technique uses a laser. The output of the laser is caused to move across a textile material. The applied energy from the laser changes the look of the textile material without undesirably burning, punching through or otherwise harming the textile material. The basic operations of applying energy from a laser are described in US Patent no. 5,990,444.

In the disclosed system, the effective applied energy of the laser, e.g, the energy density per unit time ("EDPUT") of the laser, is changed while the laser is scribing a line across the

material ("on the fly"). The line which is scribed can be a straight line or a waveform of any shape; however, a line is formed by the laser traversing the textile or garment from one edge to another.

5 The present application introduces the concept of effective applied energy. This includes the amount of energy that is effectively applied to an area of a material. That area can be any size or shape. The "effective applied energy" can include edput, but also includes changing scan line speed, power level  
10 or speed level or duty cycle level of the laser. It includes change the distance of the laser to the material, which can defocus the laser, and thereby change the EDPUT. It also includes effective applied power being applied in multiple sessions or times, by applying multiple passes, e.g. of fixed  
15 power etc. The effect is to apply more energy to some areas than to others.

Another element produces a control sequence that simulates a statistically random property of particle distribution such as would be produced by a sandblasting process. This technique is  
20 used with a user interface program, which enables the designer to paint the information on an interface screen. The image on the screen is applied to the material with a laser. Another

aspect of the technique enables use of a much higher power laser than previous systems of this type.

As described above, the amount of change that the laser produces on the textile material is based in part on the effective applied energy to the material; previously described in US patent no 5,990,444 as the energy density per unit time level of the laser relative to the material. EDPUT depends on power of the laser, spot size and scan speed of the laser system relative to the material.

A laser output of the laser is used to scribe multiple lines across the material. The line can repeat, i.e. in a zigzag or triangle wave shape. According to the present system, the EDPUT level is changed while a line is being scanned across the material. That is, at some point between the ends of at least one scan line, the EDPUT is different than it is at either end of the line. The controller system controls the change of EDPUT level by controlling the parameters which control EDPUT (power or duty cycle or speed or distance).

The EDPUT delivered to the material may be changed in different ways. A first way is to change the wattage or power of the laser output in a continuous or discontinuous fashion. A laser relies on light bouncing back and forth inside a laser

cavity. The level of excitation of the laser itself may be variable in certain lasers. Hence excitation unit 200 may actually be variable to vary the power output of the laser. Thus, this first way to change the EDPUT level of the laser  
5 directly controls the level of excitation of the laser in an analog manner.

The other EDPUT controls do not change the actual laser power output, but instead change the effective amount of energy density per time that arrives on the material. Another control  
10 of EDPUT is via duty cycle control. The control drive 198 to the excitation unit 200 can be cycled between on, and off, at a relatively quick rate. The rate of turning on and off must be fast relative to the movement of the laser. This technique changes the duty cycle of the output of the laser 205,  
15 effectively controlling the laser to deliver a different average power level. In any short time, i.e. in the amount of time it takes the laser to traverse a distance equal to one or two times the width of the laser beam, the duty cycle may be adjusted multiple times. The effective applied energy density per unit  
20 time may therefore be adjusted by this system, since the root mean square of the power varies with time just as if the power were changed itself.

The laser can also use an adjustable shutter, as shown as element 210. This shutter may use a fast piezoelectric element to open and close an aperture through which the laser beam 208 passes. The mechanical shutter can also turn on and off the shutter relatively quickly. Hence, this mechanical shutter forms an alternate way of changing the duty cycle of laser application.

The laser beam is applied to the garment and caused to move relative to the garment by a laser moving element 215. This laser moving element can include moving mirrors, or some other way of changing the laser movement. In this embodiment, the controller may also produce an output that controls the scanning speed of the laser. By changing the speed of the laser, the EDPUT changes along the course of its line, even if the output power of the laser stays constant.

Yet another way of changing the EDPUT is via changing the output size of the laser beam. Figure 2 shows a zoom lens assembly 120 which is electrically controllable. The controller 199 may produce an output signal that changes the relative position of the lenses to one another and thereby electrically changes the spot size.

Alternatively, the platform 230 holding the material may



itself be moved. Placing the garment on a curved surface is yet another way to change the EDPUT levels by intentionally causing the laser beam to come out of focus (lowering the EDPUT) at the curved sections if the center of the section is exactly in

5 focus.

Yet another way to change the EDPUT is to make multiple passes or laser scans on different segments of the pattern. Those sections which have multiple passes will have higher effective EDPUTs if all other laser operating parameters are held constant.

This system is used to attempt to mimic naturally-occurring processes. Worn looks that are obtained from a conventional laser scribing process may look overly uniform in some circumstances. This may be referred to as a contrived or pasted look. The goal, however, is to produce as natural a look as possible.

U.S. Patent No. 5,916,461 describes using a probability density function to randomly turn the laser on and off to simulate "feathering" on the material.

20 The inventors recognized, however, that continuously and discontinuously changing the EDPUT level within any laser scan line can even further improve the effect. By so doing, this

system alters the amount of change or abrasion to the textile material, as the laser scribes individual lines on the textile material. This invention provides complete control of the degree of feathering. The degree of feathering can be  
5 continuously controlled then by changing the EDPUT levels anywhere in the pattern. Control of feathering in this way can achieve a worn looks that appears authentic.

One aspect of this system, therefore, produces a worn look or other desired look on a textile material by scanning a laser across a textile, and uses the laser to change a color of the  
10 material, where the effective power density per unit time of the laser is changed at least once within a scan line.

According to one aspect, typically sandblasted garments are examined. This examination reveals different shapes and wear  
15 patterns. These patterns are basically non-uniform in nature. A high degree of feathering, or variation of the material (abrasion), across the edges and top and bottom of a pattern is observed, either directly by a human examiner, or via an automated examination process. Different concentrations of wear  
20 along different areas of the pattern are also observed. The present system stores information from this observation in the memory 195 that is associated with the controller. This

information includes geometric information about the wear pattern to be scribed. The information also includes the look of the actual scanned portion.

This look is then translated into an specified type of parameter matrix. The matrix can be an EDPUT matrix, a power matrix, a duty cycle matrix or a speed matrix, for example. The inventors have found by experimentation that the amount of energy per unit time that is applied to any specific area of certain textiles may change the look in proportion to the applied amount of energy. This proportion need not be a linear proportion. The look change may also include the look after washing.

Different patterns can hence be scanned, e.g. using a scanner or camera. The scanner can evaluate each of the sections on the garment, here shown as denim jeans. The system may evaluate, using the total resolution of the scanner, the color of that section. A look up table can be established relating the color of certain materials to the applied EDPUT or power or duty cycle or speed or distance. In this way, the EDPUT for each area on the jeans can be established.

This information can be used to form the above-described matrix, storing any of the above-described parameters. This

matrix can then be used as the information in the memory 195  
which drives the controller to drive the laser. In this way,  
different EDPUT levels can be applied to different sections of  
the textile based on the information that is obtained by

5 observing some other material.

Alternately, the user can examine the wear pattern and  
manually enter the changes in EDPUT (power, speed, duty cycle or  
distance) that are associated with the change in abrasion along  
the pattern geometry. These techniques can replicate any  
10 desired look, and can also produce an entirely new look.

In another aspect, existing looks can be edited. The look  
is scanned as noted above to form a matrix. The matrix can then  
be edited to keep the desirable parts, and change other parts.

15 Examples of the distribution of EDPUT along a single  
scanned line may look as shown in Table I.

**Table I. EDPUT Calculations for a**

**Scanned Line**

<b>Power</b>	<b>Spot</b>	<b>Area</b>	<b>Speed</b>	<b>EDPUT</b>
<b>(watts)</b>	<b>(mm)</b>	<b>(mm<sup>2</sup>)</b>	<b>mm/sec</b>	<b>watts-sec/mm<sup>3</sup></b>

Scan #1:

Start of Scan	150	0.30	0.0707	25,000	0.08
First Section of Scan	190	0.30	0.0707	25,000	0.11
First Quarter of Scan	225	0.30	0.0707	25,000	0.13
Second Quarter of Scan	250	0.30	0.0707	25,000	0.14
Middle of Scan	250	0.30	0.0707	25,000	0.14
Third Quarter of Scan	225	0.30	0.0707	25,000	0.13
Fourth Quarter of Scan	190	0.30	0.0707	25,000	0.11
End of Scan	150	0.30	0.0707	25,000	0.14

Scan #2:

Start of Scan	50	0.30	0.0707	50,000	0.01
First Section of Scan	500	0.30	0.0707	50,000	0.14
First Quarter of Scan	800	0.30	0.0707	50,000	0.22
Second Quarter of Scan	1000	0.30	0.0707	50,000	0.28
Middle of Scan	1000	0.30	0.0707	50,000	0.28
Third Quarter of Scan	800	0.30	0.0707	50,000	0.22
Fourth Quarter of Scan	500	0.30	0.0707	50,000	0.14
End of Scan	300	0.30	0.0707	50,000	0.08

Scan #3:

Start of Scan	50	0.30	0.0707	10,000	0.07
---------------	----	------	--------	--------	------

First Section of Scan	300	0.30	0.0707	10,000	0.42
First Quarter of Scan	500	0.30	0.0707	10,000	0.71
Second Quarter of Scan	1000	0.30	0.0707	10,000	1.41
Middle of Scan	1000	0.30	0.0707	10,000	1.41
Third Quarter of Scan	500	0.30	0.0707	10,000	0.71
Fourth Quarter of Scan	300	0.30	0.0707	10,000	0.42
End of Scan	50	0.30	0.0707	10,000	0.07

This table shows that the EDPUT varies from about 0.08 watts-sec/mm<sup>3</sup> to about 0.14 watts-sec/mm<sup>3</sup> for the first scan line which may produce local abrasion patterns. The EDPUT varies from about 0.01 watts-sec/mm<sup>3</sup> to about 0.28 watts-sec/mm<sup>3</sup> for the second scan line which may produce somewhat different local abrasion patterns. The EDPUT varies from about 0.07 watts-sec/mm<sup>3</sup> to about 1.4 watts-sec/mm<sup>3</sup> for the third scan line.

These latter, higher EDPUTs may be associated with more

aggressive abrasion patterns including fraying. However, it should be seen that within a certain scanned line, the EDPUT value can vary 40% or so and yet within another line, the EDPUT may vary by over 1000%. Of course, the EDPUT values can vary as little as 25% or as much as 2000% to create different worn

looks with different degrees of feathering.

In general, looking at these values, the EDPUT can increase by any desired amount. Moreover, while this system shows the EDPUT changing a few times within a scan, the EDPUT can change any number of times within a scan line. The EDPUT control is thus infinite and can vary a few percent to several thousand percent along each scanned line and from one scanned line to another.

The inventors observed that the cycle time to laze the abraded pattern on denim legs could be reduced to 8 seconds or less at a scan speed of 50,000 mm/sec by using higher power or duty cycle to maintain the intensity of the image.

Table II shows the variation in EDPUT along an individual scanned line for a different pattern.

**Table II. EDPUT Calculations for**

**Worn Pattern #2**

Power	Spot	Area	Speed	EDPUT
(watts)	(mm)	(mm <sup>2</sup> )	mm/sec	watts- sec/mm <sup>3</sup>

Worn Pattern #2:

Start of Scan	20	0.30	0.0707	10000	0.03
First Section of Scan	50	0.30	0.0707	10000	0.07
First Quarter of Scan	500	0.30	0.0707	10000	0.71
Second Quarter of Scan	500	0.30	0.0707	10000	0.71
Middle of Scan	500	0.30	0.0707	10000	0.71
Third Quarter of Scan	300	0.30	0.0707	10000	0.42
Fourth Quarter of Scan	150	0.30	0.0707	10000	0.21
End of Scan	20	0.30	0.0707	10000	0.03

Worn Pattern #2:

Start of Scan	20	0.30	0.0707	20000	0.01
First Section of Scan	50	0.30	0.0707	20000	0.04
First Quarter of Scan	500	0.30	0.0707	20000	0.35
Second Quarter of Scan	500	0.30	0.0707	20000	0.35
Middle of Scan	500	0.30	0.0707	20000	0.35
Third Quarter of Scan	300	0.30	0.0707	20000	0.21
Fourth Quarter of Scan	150	0.30	0.0707	20000	0.11
End of Scan	20	0.30	0.0707	20000	0.01

Worn Pattern #2:

Start of Scan	20	0.30	0.0707	50000	0.01
---------------	----	------	--------	-------	------



First Section of Scan	50	0.30	0.0707	50000	0.01
First Quarter of Scan	500	0.30	0.0707	50000	0.14
Second Quarter of Scan	500	0.30	0.0707	50000	0.14
Middle of Scan	500	0.30	0.0707	50000	0.14
Third Quarter of Scan	300	0.30	0.0707	50000	0.08
Fourth Quarter of Scan	150	0.30	0.0707	50000	0.04
End of Scan	20	0.30	0.0707	50000	0.01

The inventors realized that having the ability to vary  
 EDPUT or power or duty cycle along each individual scanned line  
 provides advantages of superior control of the degree of  
 feathering, and hence, the creation of an almost infinite  
 variety of worn looks. Further, the EDPUT or power or duty  
 cycle could change both along each individual scanned line as  
 well as from scanned line to scanned line. EDPUT distributions  
 such as shown in Tables III-IV could easily be achieved, along  
 with almost any other EDPUT distributions that are specified.

Table III shows a non-uniform pattern with somewhat  
 symmetrical shape along the center, whereas Table IV shows a  
 non-uniform pattern with heavier applications of power in the  
 lower left quadrant of the pattern. Hence, a greater variety of  
 EDPUT patterns and thus worn looks can be created with these

techniques.

**Table III. EDPUT (watts-sec/mm<sup>3</sup>)**

**Matrix for Worn Pattern #3**

	X Position						
	(mm)						
	0	5	10	15	20	25	30
Y Position (mm)							
0	0.05	0.1	0.2	0.3	0.1	0.08	0.02
10	0.1	0.3	0.5	0.5	0.2	0.1	0.03
20	0.2	0.4	0.7	0.7	0.3	0.2	0.1
30	0.4	0.6	0.7	0.7	0.4	0.3	0.1
40	0.4	0.5	0.7	0.7	0.3	0.3	0.1
50	0.3	0.4	0.7	0.6	0.2	0.1	0.05
60	0.2	0.3	0.4	0.5	0.1	0.1	0.03
70	0.1	0.2	0.3	0.4	0.05	0.05	0.02
80	0.05	0.1	0.2	0.3	0.05	0.03	0.01

**Table IV. EDPUT (watts-sec/mm<sup>3</sup>) Matrix**

**for Worn Pattern #4**

		X Position						
		(mm)						
		0	5	10	15	20	25	30
Y Position (mm)								
	0	0.01	0.03	0.05	0.1	0.2	0.2	0.05
	10	0.01	0.03	0.1	0.3	0.3	0.2	0.025
	20	0.05	0.4	0.7	0.6	0.6	0.5	0.09
	30	0.05	0.5	0.7	0.6	0.4	0.3	0.1
	40	0.1	0.7	0.7	0.5	0.4	0.3	0.1
	50	0.2	0.7	0.7	0.6	0.6	0.3	0.05
	60	0.1	0.6	0.6	0.3	0.5	0.1	0.03
	70	0.01	0.05	0.1	0.5	0.4	0.05	0.02

This revolutionary concept changes the "black and white" characteristic of the laser-scribed image to a new "grayscale" characteristic. In the conventional laser marking of materials

such as wood, plastic, metals, etc. the image is created at a constant EDPUT or power or duty cycle. In the case of laser marking denim, as described in the inventors earlier patents noted above, the image may be created by using a constant EDPUT  
5 on each line. Thus, one uniform color was formed after lazng and washing that was between indigo blue or black (for low EDPUT scribing) and white or gray (for high EDPUT scribing). However, the capability to continuously or discontinuously change the EDPUT allows the image to assume any shade (after washing)  
10 between indigo blue and white, along any section of the pattern.

The shade is associated with the degree of abrasion or degree of wear. Hence, the ability to control the shade also allows control of the degree of abrasion and feathering.

Further, this new flexibility can thus allow for the  
15 creation of entirely new looks not possible by any other economic means. Worn looks, images, or entirely new looks with sections of continuously or discontinuously different shades between white and indigo blue can be created. The techniques of continuously or discontinuously changing the EDPUT during laser  
20 scribing as described herein may have other applications in other material industries where lasers are used to mark materials such as wood, glass, plastic, rubber, fabric, steel

and others.

As alluded to above, this system has the ability to more accurately assess worn looks. This is done by producing a control sequence which replicates the desired properties; in an on/off manner, continuous manner, discontinuous manner or in an analog manner. Any desired amount of control can be provided, limited only by the amount of EDPUT gradations produced by the system. The general EDPUT profile can still be specified graphically, but the precise point during the scribing of a line at which EDPUT will change can also be controlled. The EDPUT profile can include a percent of the highest power or duty cycle required. As an example, 50% values may be chosen for areas requiring light abrasion and 100% values can be chosen for areas requiring heavy abrasion.

A new technique which assists the apparel designer, is disclosed. This allows the operator to paint the desired shape or geometry of the pattern desired to be lazed on the denim to obtain the worn look on the computer screen. In addition, the designer specifies the degree of feathering or EDPUT or power or duty cycle profile. Again, this specification can simply be a percent of the maximum EDPUT, power or duty cycle.

Each level of effective applied power is associated with a

color. Different sections of the pattern are painted with different color contents, where the color contents can be in full power, e.g., R,G,B levels or in gray scale levels. In one embodiment, the colors are associated with different levels of duty cycle control of the laser. The user draws on the computer screen, with the mouse, the desired shape of the pattern. Then the user can select different colors for different areas. This can use a point-and-shoot technique or selection from a menu or by right clicking on an area and selecting from a context menu.

This click associates different sections of the pattern with different EDPUT/power/duty cycle levels. The actual power level or duty cycle associated with a given color may be set by a user, and may be modified for different materials.

A local abrasion effect can be produced using the user interface screen shown in Figure 3. Figure 3 shows a graphical user interface which permits formation of a pattern, or a portion of a pattern which will form the basic design to be scribed on a garment. The actual pattern 300 is formed of a plurality of different sections. The outer section 305 defines the overall outer perimeter of the shape. Also within the sections are other perimeters shown as 310, 315, 320 and the like. The innermost shapes, such as 325, are also shown. For

shapes of this type, where the patterns define an oval pattern,  
many of the sections are concentric or semi-concentric. The  
sections can be defined by perimeters. Spaces between each two  
perimeters defines a section. Alternatively, each section can  
5 define a separate layer.

Figure 3 also shows a plurality of operating parameters  
which can be set. This includes 330, which sets the speed in  
inches per second and 332 which sets the laser scale factor in  
units per inch. The pattern scale factor 334 can also be set.  
10 The pattern dimension on the laser can be set. 338 indicates the  
drawing direction of the laser. 340 represents the color  
change. A boundary length is set in 342. For some random or  
psuedo random processes, a random seed may be necessary. This  
random seed may be set. Typical editing controls, such as edit,  
15 save, preview, etc. are also shown.

350 represents the power profile. The colors 352 are on the  
left side, and the power profile in row 354 is associated with  
that color.

The system starts with the user selecting a section, either  
20 the outermost section or any of the more inner sections that are  
shown. Each of these sections can be set as having a specified  
power profile by associating a color from the color palette 352

with a section. The power profiles represent different laser intensities (EDPUT levels) and thus different degrees of wear. For example, the lighter outer sections such as 310 and 305 may be associated with a lower power duty cycle level. This creates  
5 a more lightly worn look. The darker sections of the pattern, such as the section 325, may be associated with higher power duty cycles and represent a more heavier worn look. 325 might represent the part of the pattern that is drawn at the knee section. Different shades of gray (following washing of the garment) are shown in the areas between the two extremes. These  
10 areas represent colors of the pattern section that is between indigo blue and total white after the processing by the laser and washing of the garment. Each of these changes are displayed in color. The values can be saved in either grayscale or in  
15 full color and are stored as part of the pattern file, here shown as left.ppx.

The pattern file represents the power profile information for the specified pattern which is displayed and editable via the user interface.

20 Additional processing features are also used to give the pattern a more realistic look. A tool set, shown as 360, can be selected to carry out these functions. A first tool which is



described herein is the blend function. Blend can be carried out either pixel by pixel, or area by area. The specific area which is blended may be selectable. A blend computes an average color for each pixel or area by forming a weighted average of the  
5 color of the pixel or area and the color of neighboring pixels or areas, e.g. eight neighboring pixels or areas. The number of pixels forming the weights can be varied to achieve various outcomes.

Another tool, shown herein as the whisker tool, may aid in  
10 whisker generation. Users may set the length and angle of the whisker, and then automatically produce a whisker pattern which can be later edited by the user.

A "grain" tool is shown as part of 360 which produces a "grainy" look. The process for the grainy look gives each  
15 pixel, and its neighboring pixels, a color vote. The weight for each vote depends on how long the pixel has maintained the specified color. The terminology of "long" can refer to number of units of image in an area, for example. Again, while this system refers to colors, it should be understood that gray  
20 scales can also be used to view the separated sections. The sections can also be marked with other area delimiters, such as hatching, stippling or the like.

Another tool developed as part of this invention is a  
"blaster" tool. In a manner similar to that used by the "spray  
can" tool supplied with many computer drawing programs to  
"spray" a specific color, the blaster tool sprays "incremental  
5 intensity" onto the pattern. To continue with the analogy,  
every time a "droplet" from the spray can hits the drawing  
surface, the pixel or area that is hit adopts the color being  
sprayed. With the blaster tool, a pixel hit by a droplet of  
incremental intensity has its color level incremented to the  
10 next higher level. The effect of the tool produces an effect  
whose impact is dependent on an amount of time spent "blasting"  
a given region. A longer period of blasting causes more pixels  
to be colored with the effect and hence causes a greater impact.

15 The blaster tool can also be used in an intensity-removing  
mode. In this mode, pixels that are hit have their color level  
changed to the next lower intensity level.

Any pattern that is formed by natural wear can be  
accurately simulated through the use of the blaster tool.

20 Furthermore, this tool can be automated to draw certain common  
features automatically, for example, a curved line simulating a  
whisker, a pocket wear pattern and the ladder pattern that

appears along the seams of worn jeans.

An "undo" function allows one or many functions to be reversed if the user does not like the effect. This can, for example, allow trying different sprays or other effects to test  
5 if a good result is obtained. If not, the operation is reversed.

This system can produce a number of different effects. Communication of pattern parameters from the design computer to the laser control computer may be used to develop an efficient

10 system. Many formats have been developed for computer viewing, generation and transmission of graphic images. The format for these files may allow for a higher degree of image complexity (e.g., color) than required for the present purpose and therefore tend to provide more information and details than is  
15 needed for the present purposes.

A new file format has been developed called TBF (TechnoBlast Format) which communicates precisely those parameters required for converting the desired image into laser control commands.

20 The file in the "TBF" format may be a bit-mapped format of a matrix. Each value represents power level/duty cycle/EDPUT for each pixel in the image as well as other control values.

This file format therefore includes an edput value, or at least a value indicative of the amount of effective energy to be applied to a pixel associated with each pixel or group of pixels that is handled as a unit.

5        Since the information can be stored on a pixel by pixel level, the writing laser can write in either the horizontal or the vertical direction, or in any other direction for that matter, based on the same information. The direction of writing can be selected by the drawing direction 38. Assuming the  
10        writing is in the horizontal direction, the image is sliced into pixel-wide fragments. The slice 370 shows, in exaggerated form, one of these pixel wide fragments. It should be understood, however, that these pixels are not drawn to scale, and that in fact a real pixel could be of any desired size. Note that each  
15        pixel such as 372, 374 may have a different EDPUT level associated with it. The EDPUT level is changed as the laser is scanning from pixel to pixel.

Many different kinds of looks can be produced using this system. The following describes only examples of these looks.

20        It should be understood that other effects could easily be produced. Any of these looks can be obtained in any of the ways described herein, i.e., by authoring a special image intended

for use in changing the color of textile fabric, or by scanning  
a real garment and using the results of the scan to form  
information to use in changing the color.

Figure 4 shows a localized worn look which extends from  
5 somewhat below the waistband to the somewhat below the knee on  
each denim leg. The color of the worn look (after washing)  
varies from white or gray in the intense areas of the knee shown  
as 402 to black or blue indigo (less intense areas) along the  
top, bottom and side portions of the knee shown as 404.

Figure 5 shows an alternative look which is intended for  
10 use in the rear portion of the denim, e.g. in the seat area.  
Again, this portion is substantially oval shaped, but has some  
worn portions in the center 502 and less worn portions towards  
the edge 504.

15 Figure 6 shows a global worn look from the waistband to the  
end of the leg section where the color of the worn look (after  
washing) ranges from white or gray in the intense areas along  
the center and length of the pattern to indigo blue or black  
along the top, bottom and edges of the pattern.

20 Figure 6 also shows the global worn look from the rear  
waistband to the end of the leg section, where the color of the  
worn look changes from white or gray in the intense areas of the

pattern to indigo blue or black along the top, bottom and edges of the pattern.

Figures 7 and 8 show a whisker worn look with multiple lines from about 1/8 inch to about 2 inches in width by 1 to 14 inches in length. The color of the pattern changes from white or gray in the center of the pattern to indigo blue or black along the edges of the pattern. The whisker worn look can be along any area of the front and back of the denim jeans and may contain one or several rectangular sections.

A frayed look in the knee, rear seating area, along the bottom of the front and back leg section or any other area of the denim jean is shown in Figures 9-10. The EDPUT is of sufficient magnitude to fray the denim so that individual threads are exposed or actual holes are provided in the denim.

This goes against the teaching in the above '444 patent, which teaches that punch through of the material is undesired. The specific "fraying" effect, provides enough EDPUT to intentionally cause damage to the material, however in a controllable and desired fashion.

A rectangular worn pattern of about 2 inches by 4 inches along the rear pocket of the denim is used to simulate the wear from a wallet in the back pocket, where the color of the pattern

is white or gray along the periphery of the rectangle and indigo, blue or black in the center. Figure 11 shows the TechnoBlast pattern image created for this type of look.

Any or all of these looks may be combined into a single  
5 image. The composite image may then be used to laze denim jeans.

This may represent an additional benefit of this system. In previous systems, different processes were used to obtain different effects. For example, conventional sandblasting is used to produce local abrasion on front and back denim leg sections. Whiskers are made using a hand sanding operation where individual laborers produced the various whisker patterns. Frayed looks use hand sanding drills and the like. In this system, however, multiple effects can all be included within the same file. For example, Figure 12 shows a composite file  
10 including a plurality of the effects shown above. An additional effect, in which the whiskers are shadowed, is shown as 1202 in Figure 12. Just above or below the whisker, a section is colored white. This indicates no lazing in that section such that after washing the area is denim blue. The whisker itself  
15 can be different colors to produce different feathering effects.

This technique produces a shadowed effect for the whiskers considered quite desirable.

Previous systems of this type have used relatively low power lasers, e.g. from 25 to 100 watts, of the type intended for marking materials. Marking lasers have been used to form graphic images and text on plastic, wood, steel and glass.

5 Another kind of laser, called the laser cutter, typically produces much higher powers, e.g. 250 to 2500 watts. One problem noted by the inventors is the cycle time for applying the worn pattern. When the low power lasers have been used, the cycle time may be on the order of minutes for each application.

10 The present application describes the use of a much higher power laser, e.g. a laser having a power level of 250 watts or higher, even more preferably 500 watts or higher, and most preferably 1000 watts or higher. For example, a cycle time for abrading denim jeans can be minutes with a 50 watt laser that is typically used for marking. A 500 watt laser can produce the same pattern in a few seconds. This 500 watt laser has typically only been used for cutting operations, however. The expectation is that these higher power lasers would  
15  
20 unintentionally damage the material. However, by adjusting the EDPUT, higher power lasers can safely be used.

As a specific example, the inventors were able to use the



500 watt lasers to laze abrasion patterns on the front and rear sections in 15 seconds as compared with two minutes for the sand blasting process. Using 2500 watt lasers for the application area is also contemplated, which will decrease the cycle time  
5 even further.

Additional developments were made during initial trials with high-powered lasers. One noted problem is that the desired level of power or duty cycle at the beginning of the scribing of a line can be higher than requested, here called an overshoot.

10 The physical nature of the laser process requires that when changing from a lower level of power or duty cycle to a higher level of power or duty cycle, "inertia" of the power may cause the power or duty cycle to initially overshoot the desired higher power or duty cycle. This may cause an initial excess  
15 visible impact on the denim target. This effect may be strongest when the laser is actually turned from off (zero power) to on. The effect on denim becomes much more evident when higher power lasers are used, e.g. 500 watts or higher.

To overcome this problem, a boundary solution is used.

20 The desired pattern is given a "boundary" area. The laser power is set to a level x that is as high as possible without causing any visible effect on the denim or other garment material. The

laser output is brought to a position outside the boundary.  
Since the laser is at the power level x, this causes no visible  
change. When the laser beam enters the region of desired  
visible impact, the effective power level is increased. The  
5 effective power level is increased less at that time, since the  
increase is from x to the desired level, rather than from 0 to  
the desired level. Overshoot from initial turn on may be  
reduced in this way.

Another important feature noted by the present application  
is based on the interference based on the pattern/lines that are  
scribed by the laser, and the direction of the materials stitch  
lines. Certain undesirable "interference patterns" may be  
produced by the interaction between the laser writing  
properties, the frequency of the laser and the directional  
15 properties of the material. These directional properties can  
include any aspect of the material that is asymmetric - and  
specifically can include cut, fill and twill of the denim  
fabric. A rotation of the fabric or the scribing direction may  
change this effect. Orienting the material such that the scan  
20 line makes a 90 degree angle with the cut, fill or twill  
minimizes the effect, when it is desired to minimize that  
effect. However, some of the interference patterns themselves

produced quite interesting looks for denim jeans, and may be desirable. Hence, one aspect of this system includes taking into account the effects of the interaction between the laser scanning and the directional properties of the material.

5       Hence, another parameter of this system requires the directional pattern of the material to be placed in a specified orientation. This can also be controlled by changing the drawing direction using control 338. One other aspect uses a camera vision system pointed to face the material and to automatically detect the directional properties of the material.

Those properties are then input into the computer, and used as one parameter of operation.

As mentioned previously, it is highly desirable to avoid an artificial or contrived look when attempting to simulate natural

wear. It is therefore useful to minimize the opportunity for the

20 human eye to perceive any regularity in the pattern produced by the laser. One approach to achieving this is to allow the user to specify the power levels in the design, but to cause the precise point at which power changes between two adjacent levels to be determined at random. This feature may not always  
30 be desirable. Hence, randomization of power level change is a

user selectable option.

The higher power lasers can operate faster, and therefore  
5 benefit from more automated processes. The conveyer system  
shown in Figure 1 provides the denim jeans 100 over some form  
102. The denim jeans are introduced to the laser in a  
horizontal direction. The laser then scribes the worn look,  
after which a second pair of jeans shown as 110 are maintained  
10 behind it and also introduced for subsequent processing. After  
processing a batch of jeans in this manner, they can be removed  
from the form and reversed to either the same or different laser  
to scribe the worn look on the rear. Figure 1 also shows an in-  
line material processing system, including an inline laundry  
15 device 120, e.g, a system that applies shampoo with a brush, and  
a removal system, such as a wet vac 130. This can use  
components from commercially available rug cleaning systems,  
e.g. a rug doctor™ or similar shampoo/vacuum combination can  
produce a desired effect with an in line system.

20 Figure 1 shows a straight path conveyer system. However, a  
carousel type conveyor is contemplated.

An alternative system is shown in Figure 13. The jeans  
1300 are located on a form shown as 1302. The form holds the

jeans in some way e.g. using clips on the inside shown as 1304,  
1306. These clips hold the denim jeans in place on the form.  
Each of the forms also include a rotation rod 1308 connected to  
a rotator 1310. The jeans are conveyed along the conveyer 1312,  
5 which includes at least two of these rotators, the second one  
being shown as 1315. At a first location, the jeans come into  
contact with a first laser 1320. This laser produces the worn  
look on the front of the jeans shown as side 1. After so doing,  
the rotator 1308 is lifted up and causes the jeans to be flipped  
10 to side 2. Subsequently, side 2 comes into contact with the  
second laser 1330 which scribes the rear worn look. The jeans  
are removed from the form after processing, and a new pair of  
unprocessed jeans applied to the form. While this system  
describes using two lasers, it should be understood that a  
15 single laser could be used, i.e. by scribing the front side of  
one or multiple pair of jeans, and later flipping all the jeans  
and scribing the other side. An automated system can detect  
whether the front or back is being presented, e.g. by imaging  
the garment to look for the label or bar code on the jeans. A  
20 camera vision system can key in on a specific area of the jean  
such as the waistband each time and simply adjust the laser scan  
to insure proper placement of the image on the denim each time.

Figure 14 shows yet another system. The jeans are held from their sides by clipping on a clip area to a specified location, e.g. the inside of the pocket where minimal denim processing will take place. Other clip areas are also possible. The materials processing system carries the denim by the clip areas, e.g. by a wire which is constantly moving.

Alternately, a form of the type shown in Figure 13 can be used as free standing conveyer system. In this embodiment, dual lasers are used, with one on the top scribing the worn look on the top surface 1400 of the jeans and the other laser 1420 on the bottom, scribing the worn look on the bottom surface of the jeans 1405. Any free standing conveyer system can be used for this. For example, this may also be done with the garment suspended on a hanging system in the vertical direction. Different form shapes are also possible.

Different type of worn looks may be obtained depending upon the type of form that is used. For example, typical metal forms such as used in the dry cleaning industry produce a worn look that is similar to that obtained from sandblasting, since the garment is relatively flat as the laser scribes the worn look on the garment. However, using an inflatable balloon type form,

such as used in some denim finishing plants, produces a somewhat different worn look. The balloon is inflated inside the denim pant leg, causing the fibers to be spread. The jean wraps around the form in a concave fashion during scribing.

5       The inventors noted that this invention produced benefits in the production of denim jeans with whisker patterns to simulate the creases along the thigh and knee section. Denim manufacturers have tried numerous methods to create the desired whisker patterns. Many have noted that only the hand sanding process was really acceptable to create the authentic worn look for the whiskers. This process may be labor intensive and the quality of the whisker pattern is a function of the skill of the laborer who sands the whiskers on the denim. Considerable variability exists from one laborer to another, as would be expected. Some laborers apply too much pressure and some too little pressure such that the quality of the end product is quite variable.

10  
15  
20       However, the inventors noted that using the new technique of changing the EDPUT along the individual scribed lines, any desired whisker pattern could be exactly replicated. Further, a typical whisker pattern could be applied to the denim jeans with this invention in a few seconds, compared to several minutes

with the hand sanding operation. The quality of the whisker pattern produced from this system is consistent from one denim jean to the other because of the consistency of the laser scribing process. Hence, the yield would be expected to be  
5 significantly greater with this invention compared with the hand sanding operation.

Although only a few embodiments are disclosed, other modifications are possible and are intended to be encompassed within the following claims. For example, other marking  
10 elements, that is other marking elements besides a laser, are contemplated.



What is claimed is:

1        1.    A method comprising:  
2            defining a pattern to be formed on a textile material,  
3    which pattern represents different degrees of change of said  
4    textile material at different locations, said different degrees  
5    of change including at least a plurality of different levels of  
6    change; and  
7            producing a viewable display representing said pattern.

1        2.    A method as in claim 1 wherein said pattern includes  
2    effective applied power density information which enables said  
3    change to be carried out with a laser.

1        3.    A method as in claim 2 wherein said applied power  
2    density levels are individually associated with different  
3    portions of said pattern, and include information which changes  
4    an energy density per unit time applied by the laser.

1           4.    A method as in claim 1 further comprising using a  
2   laser to scan lines defining said pattern onto a garment, by  
3   controlling said laser according to said pattern to apply energy  
4   across different lines which are produced across the pattern, at  
5   least one of said lines including plurality of different  
6   effective applied energy on a single line.

1           5.    A method as in claim 1 wherein said viewable display  
2   includes a plurality of different sections, and further  
3   comprising accepting commands on a user interface that enable  
4   each of said sections to be separately controllable on said  
5   viewable display, to produce a different degree of viewed change  
6   on said viewable display.

1           6.    A method as in claim 5 further comprising converting  
2   said sections to scan lines in a desired direction, and using a  
3   laser to produce a desired effective applied energy based on  
4   said pattern, to produce a desired output along said scan lines,  
5   at least one of said scan lines having a different effective  
6   applied energy at a central portion as compared with at either  
7   end portion thereof.

1           7.    A method as in claim 6 wherein said scan line is a  
2 horizontal scan line.

1           8.    A method as in claim 6 wherein said scan line is a  
2 vertical scan line or any angled scan line.

1           9.    A method as in claim 6 wherein said using a laser  
2 comprises changing an effective power output of the laser while  
3 scanning a line.

1           10.   A method as in claim 9 wherein said changing effective  
2 power comprises control of the power level via duty cycle  
3 control.

1           11.   A method as in claim 10 wherein said duty cycle  
2 control turns on and off the laser at a specified rate in a  
3 pulsed manner.

1           12.   A method as in claim 10 wherein said duty cycle  
2 controls blocks and unblocks the output of the laser at a  
3 specified rate.

1        13. A method as in claim 9 wherein said changing comprises  
2 changing a spot size of the beam.

1        14. A method as in claim 1 wherein said defining comprises  
2 examining an existing garment to determine a pattern of  
3 abrasion, and  
4 forming said pattern based on said examining.

1        15. A method as in claim 14 wherein said forming comprises  
2 automatically forming said pattern.

1        16. A method as in claim 14 wherein said examining  
2 comprises using a scanner to determine color contents of a  
3 section of material, and automatically translating said color  
4 contents into an a value indicative of effective applied energy.

1        17. A method as in claim 16 wherein said translating  
2 comprises using a look up table to change said color contents  
3 into said value indicative of effective applied energy.

1 18. A method as in claim 1 further comprising using said  
2 pattern to control a laser having a total power of 500 watts or  
3 greater; and using said laser to form said pattern on a garment.

1 19. A method as in claim 1 further comprising using said  
2 pattern to control a laser having a total power of 1000 watts or  
3 greater; and using said laser to form said pattern on a garment.

1 20. A method as in claim 4 wherein said power of the laser  
2 changes by a factor of at least 25% during a single scan line of  
3 said laser.

1 21. A method as in claim 4 wherein said effective applied  
2 energy changes by at least 25% during a single scan line of  
3 said laser.

1 22. A method as in claim 1 wherein said defining comprises  
2 determining a desired shape for a pattern portion, and painting  
3 color contents on said shape being displayed.

1        23. A method as in claim 22 wherein said color contents  
2 represent a degree of abrasion to a specified area on said  
3 garment.

1        24. A method as in claim 22 further comprising defining a  
2 plurality of parameters to be associated with a portion of said  
3 pattern, and defining a section between any two parameters, each  
4 said section being separately changeable.

1        25. A method as in claim 1 further comprising defining  
2 effects for portions of the pattern.

1        26. A method as in claim 25 wherein said effect is a blend  
2 function which computes an average color for pixels based on  
3 colors of a pixel and colors of a neighboring pixel.

1        27. A method as in claim 1 wherein said pattern is a  
2 pattern of a whisker pattern.

1        28. A method as in claim 25 wherein said effect is a grain  
2 look which allows different colors to have different votes.

1           29. A method as in claim 25 wherein said effect is a spray  
2 look.

1           30. A method as in claim 1 wherein said pattern is a  
2 pattern is a pattern on a garment, only on a specified portion  
3 of the garment, in a location from below the waist to below the  
4 knee on the garment.

1           31. A method as in claim 1 wherein said pattern is the  
2 pattern of a worn seat look on a garment.

1           32. A method as in claim 1 wherein said pattern is oval  
2 shaped with a plurality of concentric portions.

1           33. A method as in claim 1 wherein said pattern includes a  
2 pattern of frayed areas in which actual holes or exposed fibers  
3 will be formed by a laser scribing using said specified  
4 parameters.

1           34. A method as in claim 1 further comprising forming a  
2 plurality of power levels for a plurality of scan lines to form  
3 said pattern, each said power levels represented by a percent of  
4 a maximum power that can be applied.

1           35. A method as in claim 34 wherein at least one of said  
2 scan lines includes an overshoot protection.

1           36. A method as in claim 35 wherein said overshoot  
2 protection includes, at an area outside the desired area of  
3 changing the image, which is set to a specified effective  
4 applied power level which is low enough to prevent change to a  
5 material to which the laser is being applied, and application of  
6 the specified effective applied power level until reaching an  
7 area of desired change, and increasing the power at said area of  
8 desired change to a level at which change to the material will  
9 be formed.

1           37. A method as in claim 1 further comprising defining an  
2 orientation of a weave line of the material as part of said  
3 display.



1 38. A method as in claim 1 further comprising passing a  
2 garment along a conveyer; and using a laser to lase an effect  
3 thereon based on information in said pattern.

1 39. A method as in claim 38 further comprising lasing a  
2 first pattern on a first side of the material on the conveyer,  
3 automatically changing the material to expose a second side to  
4 a laser and then automatically lasing another pattern, different  
5 than the first pattern, on the second side of the material.

1 40. A method as in claim 34 wherein at least a portion of  
2 the lasing is carried out at a level of effective applied power  
3 which does not undesirably damage the material.

1 41. A method comprising:  
2 storing information about effective applied power levels  
3 for a plurality of scan lines of a laser element, at least a  
4 plurality of said scan lines having levels of effective applied  
5 power which change within a single scan line; and  
6 using a laser to process the material by controlling scan  
7 lines of the laser to have a controlled energy density per unit  
8 time which depends on said effective applied power levels.

1           42. A method as in claim 41 wherein at least a plurality  
2 of said effective applied power levels are values which do not  
3 undesirably damage the material.

1           43. A method as in claim 42 wherein at least a plurality  
2 of said effective applied power levels are values which  
3 intentionally cause a hole in the material to cause fraying.

1           44. A method as in claim 41 wherein said file is  
2 indicative of a simulated abrasion effect to create a worn look.

1           45. A method as in claim 41 wherein said information is  
2 indicative of simulated whisker effect.

1           46. A method as in claim 41 wherein at least part of said  
2 information is indicative of a simulated fraying effect.

1           47. A method as in claim 41 wherein said garment is a  
2 denim garment.

1           48. A method as in claim 41 wherein said laser has an  
2           output power of 500 watts or greater.

1           49. A method as in claim 41 wherein said laser is one  
2           which has an output power of 1000 watts or greater.

1           50. A method as in claim 41 wherein said pattern is an  
2           oval shaped pattern.

1           51. A method as in claim 41 wherein said control of  
2           effective applied power levels is carried out by control of duty  
3           cycle of said laser thereby controlling an effect of amount of  
4           power delivered by the laser in a pulsed manner.

1           52. A method as in claim 51 wherein said control of duty  
2           cycle comprises turning a laser on and off at specified rate.

1           53. A method as in claim 52 wherein said specified rate is  
2           fast relative to the movement of the laser.

1           54. A method as in claim 51 wherein said control of duty  
2 cycle comprises selectively blocking and unblocking an output of  
3 the laser to thereby control an effective amount of power  
4 delivered by the laser.

1           55. A method as in claim 41 further comprising changing  
2 the EDPUT by changing a speed of movement of the laser.

1           56. A method as in claim 41 wherein said change of  
2 effective applied power levels comprises changing an output size  
3 of a laser beam that is output from the laser.

1           57. A method as in claim 41 further comprising feathering  
2 an edge of the pattern by changing a power level of the image at  
3 said edge to form a more gradual change of effect at said edge.

1           58. A method as in claim 41, wherein said information is in  
2 a specified format, which includes an indication of an area and  
3 an indication of an effective applied power level to be applied  
4 to said area.

1        59. An apparatus, comprising:  
2        a computer controlled laser, having an output which  
3        impinges on a surface to be modified by said laser and which is  
4        controlled according to a computer file, said computer  
5        controlled laser producing said output beam having a controlled  
6        effective applied power level of application to the area,  
7        according to said computer file, wherein said computer file  
8        includes at least a plurality of scan lines in which said  
9        effective applied power level changes within a single scan line  
10       at least three times to at least three different values.

1       60. An apparatus as in claim 59 wherein said laser has a  
2       power output of 500 watts or greater.

1       61. An apparatus as in claim 59 wherein said laser has a  
2       power output of 1000 watts or greater.

1           62. An apparatus as in claim 59 wherein said effective  
2 applied power level is selected for a specific textile material  
3 to be lased, and at least one of said effective applied power  
4 levels in said computer file changes the look of the textile  
5 material without undesirably burning, punching through or  
6 otherwise harming the textile material.

1           63. An apparatus as in claim 62 where at least one of the  
2 effective applied power levels in said computer file does cause  
3 burn through of the material to expose fibers in the material.

1           64. An apparatus as in claim 62 further comprising an in-  
2 line shampooing element, which provides a shampooing operation  
3 and a shampoo removal operation to a garment which has been  
4 lased by the laser.

1           65. An apparatus as in claim 59 wherein an effective  
2 applied power level of the laser is changed by turning on and  
3 off the laser at a specified duty cycle.

1        66. An apparatus as in claim 59 further comprising an  
2 adjustable shutter which modulates an output of the laser, and a  
3 control element which turns on and off said shutter, based on  
4 said computer file, to adjust said effective applied power  
5 level.

1        67. An apparatus as in claim 66 wherein said shutter is a  
2 piezoelectric element.

1        68. An apparatus as in claim 66 wherein said shutter is a  
2 mechanical shutter.

1        69. An apparatus as in claim 59 wherein said effective  
2 applied power level changes to at least five different values in  
3 at least a plurality of scan lines of said laser.

1        70. An apparatus as in claim 59 wherein said effective  
2 applied power level changes between a lowest value and a highest  
3 value, wherein said highest value is at least 125% of said  
4 lowest value.

1        71. An apparatus as in claim 59 wherein said effective  
2 applied power level changes between a lowest value and a highest  
3 value, wherein said highest value is at least twice said lowest  
4 value.

1        72. An apparatus as in claim 59 wherein said pattern  
2 includes a feathering portion at an edge of the pattern where a  
3 change in effective applied power level is made gradual to  
4 gradually change an effect thereof.

1        73. An apparatus as in claim 59 further comprising a  
2 control console, having a user interface, said user interface  
3 graphically showing a pattern which is to be lased, said pattern  
4 including differently highlighted areas for different effective  
5 applied power levels.

1        74. An apparatus as in claim 73 wherein said differently  
2 highlighted areas comprise different colors.



1        75. An apparatus as in claim 59, wherein said computer  
2 file includes a plurality of information parts, each information  
3 part associated with a specific area on an image representing a  
4 garment to be altered, and each information part including  
5 information indicating effective applied power level information  
6 for a laser.

1        76. An apparatus as in claim 73 wherein said differently  
2 highlighted areas comprise different gray scales.

1        77. An apparatus as in claim 74 further comprising a look  
2 up table which stores a relationship between an effect to a  
3 material, and a duty cycle of operation of the laser to provide  
4 said effect.

1        78. An apparatus as in claim 74 further comprising an  
2 editing tool which enables editing said pattern.

1        79. An apparatus as in claim 59 wherein said memory stores  
2 a pattern of a simulated worn pattern.

1        80. An apparatus as in claim 59 wherein said pattern  
2 stores a simulated whisker pattern.

1        81. An apparatus as in claim 59 wherein said pattern  
2 stores a pattern with a hole through the denim of a type which  
3 exposes fibers of the denim.

1        82. An apparatus comprising:  
2        a controllable laser, which is controllable by a computer  
3 file, to produce an output on a desired area, said laser having  
4 a maximum output power which is 500 watts or greater; and  
5        said computer file storing control information which  
6 adjusts a duty cycle of an output of said laser to control an  
7 effective applied energy applied to said area to a desired  
8 amount and providing said information for a desired energy  
9 density per unit time to said controllable laser for said area.

1        83. An apparatus as in claim 82 wherein said laser is  
2 controlled to scan in lines, and wherein a plurality of said  
3 lines have different effective applied area at one area than in  
4 another area.

1        84. An apparatus as in claim 83 wherein said effective  
2 applied energy changes to at least three different values within  
3 a single scan line.

1        85. An apparatus as in claim 82 wherein at least some of  
2 said effective applied energies is set to a specific value  
3 relative to a material in said area, which changes the abrasion  
4 or color of said material without undesirably damaging the  
5 material.

1        86. An apparatus as in claim 82 where at least part of  
2 said effective applied energies provides a desired punch through  
3 effect in said material.

1        87. An apparatus as in claim 82 further comprising a  
2 terminal, which provides an image of the simulated pattern to be  
3 applied to the material, said image having differently indiciaed  
4 areas to represent different effective applied energies.

1        88. An apparatus as in claim 87 wherein said indiciaed  
2 areas comprise differently colored areas.

1        89. An apparatus as in claim 87 wherein said indiciaed  
2 areas comprise different grayscales.

1        90. An apparatus as in claim 82 further comprising a duty  
2 cycle controller comprising and on off control for the laser.

1        91. An apparatus as in claim 82 further comprising a duty  
2 cycle controller comprising a shutter, selectively opened and  
3 closed at an output of the laser.

1        92. An apparatus as in claim 87 wherein the stored pattern  
2 has a plurality of concentric oval areas.

1        93. A method of processing a garment, comprising:  
2        obtaining a first garment which has a desired look to be  
3 replicated;  
4        using an electronic device to capture color levels of  
5 different areas of said first garment;  
6        automatically determining, from said color levels, an  
7 amount of effective applied energy of laser energy which will  
8 need to be applied to said each of said area to replicate said  
9 color level; and  
10       forming a computer file representing said amount of laser  
11 power which needs to be applied to each of said areas to  
12 replicate said different areas of said first garment.

1       94. A method as in claim 93 further comprising using said  
2 computer file to control a laser to mark a second garment in a  
3 way that replicates a pattern of the colors on the first  
4 garment.

1       95. A method as in claim 94 wherein said laser marks said  
2 second garment by scribing a plurality of lines on said second  
3 garment using said computer file.

1        96. An apparatus as in claim 95 wherein at least a  
2 plurality of said lines define an effective applied energy which  
3 varies within each of a plurality of single scanned lines.

1        97. An apparatus as in claim 96 wherein said effective  
2 applied energy varies to at least three different values within  
3 said plurality of lines.

1        98. A method as in claim 94 wherein said translating  
2 comprises using a look up table which stores a correspondence  
3 between a specified color and a specified effective applied  
4 energy, to determine said power levels.

1        99. A method as in claim 94 further comprising storing  
2 information in a look up table, and using said information to  
3 determine said effective applied energy for each of said areas.

1 100. A method as in claim 94 wherein said using a laser  
2 comprises adjusting said effective applied energy by adjusting a  
3 duty cycle of an output of said laser at a speed which is fast  
4 relative to a speed of movement of said laser, and in a way  
5 which adjusts an effective power output of said laser within a  
6 single scan line.

1 101. A method as in claim 100 wherein said duty cycle  
2 control comprises turning the laser on and off at a specified  
3 rate.

1 102. A method as in claim 100 wherein said duty cycle  
2 control comprises selectively blocking and unblocking an output  
3 of the laser.

1 103. A method as in claim in 94 wherein said laser has an  
2 output power of 500 watts or greater.

1 104. A method as in claim 93 further comprising displaying  
2 a graphical image indicative of said computer file to a user and  
3 allowing said user to edit said graphical image to thereby edit  
4 said computer file.

1           105. A method as in claim 104 wherein different areas of  
2   said computer file have different indicia indicative of  
3   different amounts of power to be applied to said area.

1           106. A method as in claim 95 further comprising allowing  
2   setting a direction of line scribing by said laser.



1        107. A method comprising:  
2        determining information indicative of a desired abrasion  
3 pattern to be formed on a garment;  
4        storing, in a memory, a relationship between each of a  
5 plurality of desired areas of abrasion and an effective applied  
6 power to be used with a specified laser to create said level of  
7 abrasion;  
8        accessing said relationship, using said information  
9 indicative of said desired abrasion pattern, to determine said  
10 effective applied power; and  
11        forming a computer file using said effective applied power  
12 and said desired pattern, said computer file including an  
13 indication of an area, and an indication of information which  
14 will cause said specified laser to apply said effective applied  
15 power in said area.

1        108. A method as in claim 107 wherein said effective  
2 applied power is an indication of a duty cycle of an output of  
3 said laser.

1           109. A method as in claim 107 further comprising displaying  
2 a graphical representation of said computer file to a user,  
3 where different indicias in different areas of said image  
4 represent different amounts of abrasion; and enabling said user  
5 to edit said graphical representation.

1           110. A method as in claim 109 wherein said indicias  
2 comprise different colors, each color associated with a  
3 specified power level and associated with a specified degree of  
4 abrasion.

1           111. A method as in claim 107 further comprising using a  
2 laser to apply said desired effective applied power level to a  
3 desired garment.

1           112. A method as in claim 111 wherein said using comprises  
2 defining lines that the laser will follow in scanning the image,  
3 and wherein at least a plurality of said lines have a varying  
4 effective applied power within the specified line.

1        113. A method as in claim 112 wherein at least a plurality  
2 of the lines have an effective applied power that varies at  
3 least three values within the scanning of the line.

1        114. A method as in claim 112 wherein said using comprises  
2 adjusting a duty cycle of the laser to change an amount of  
3 effective applied power that is applied.

1        115. A method, comprising:  
2        defining a desired pattern of color alterations to be  
3 formed to a garment by selecting a plurality of areas on a  
4 display, defining a color that is associated with each of a  
5 plurality of abrasion levels, selecting a color to associate  
6 with each of the plurality of areas to thereby associate a level  
7 of abrasion with each of the plurality of areas; and  
8        storing a computer file indicative of said selecting.

1        116. A method as in claim 115 further comprising enabling  
2 said display to be edited, to change color and or shape.

1 117. A method as in claim 116 wherein said computer file  
2 specifies information for use in forming control data for a  
3 laser to scribe lines on a desired garment, wherein at least a  
4 plurality of said lines specify an energy density per unit time  
5 which changes within a single scan line.

1 118. A method as in claim 117 wherein at least a plurality  
2 of lines have an energy density per unit time which has at least  
3 three values within the specified line.

1 119. A method as in claim 118 wherein a highest of said  
2 three values is at least 1.25 times as high as a lowest of said  
3 three values.

1 120. A method as in claim 116 wherein said editing  
2 comprises applying an abrasion using a spray tool.

1 121. A method as in claim 116 wherein said editing  
2 comprises decreasing a resolution of said image.

1 122. A method as in claim 115 further comprising storing,  
2 in a memory, a relationship between each color and an amount of  
3 effective applied energy representing the color.

1 123. A method as in claim 116 wherein said using a laser  
2 comprises controlling the laser to control an effective applied  
3 power applied to an area by controlling a duty cycle of the  
4 laser.

1 124. A method as in claim 123 wherein said duty cycle is  
2 controlled by selectively blocking and unblocking an output of  
3 said laser.

1 125. A method as in claim 123 wherein said duty cycle is  
2 controlled by turning on and off the laser.

1 126. A method, comprising:  
2 defining an image of a whisker part which represents an  
3 image of a color change to a material caused by creasing of the  
4 material; and  
5 using a laser to simulate the look of said whisker part on  
6 the material.

1           127. A method as in claim 126 wherein said whisker part  
2 comprises a plurality of lines that represent the creases.

1           128. A method as in claim 127 wherein each of the whiskers  
2 are between 1/8th of an inch and 2 inches in width and between  
3 one and ten inches in length.

1           129. A method as in claim 126 wherein each of the lines is  
2 a different color in the center then along the top, bottom and  
3 towards its edges.

1           130. A method as in claim 126 wherein said forming  
2 comprises allowing a user to form a desired view of the whisker  
3 on a user interface; and  
4           converting the image on the user interface to a computer  
5 file used to control the laser.

1           131. A method as in claim 126 wherein said forming the  
2 whisker comprises using a laser having a maximum output power of  
3 500 watts or greater to form a pattern.

1 132. A method as in claim 131 wherein said pattern is  
2 formed in a way which does not undesirably damage the material.

1 133. A method of processing a garment, comprising:  
2 defining a desired pattern to be formed on the garment and  
3 producing a computer file indicative thereof;  
4 using said computer file with a laser having a maximum  
5 output power of 500 watts or greater, to scribe the desired  
6 pattern on said garment; and  
7 using said laser for thirty seconds or less to form said  
8 entire pattern.

1 134. A method as in claim 133 further comprising  
2 controlling an effective output power of said laser by  
3 controlling a duty cycle of operation thereof.

1 135. A method of forming a pattern on a garment comprising:  
2 determining a pattern to be formed on a garment;  
3 determining an effect that a directional characteristic of  
4 the material will have on the pattern to be formed; and  
5 specifying both said pattern and said directional  
6 characteristic.

1 136. A method as in claim 135, wherein said specifying  
2 includes forming a computer file indicative of areas, and  
3 effective power output levels associated with each said area.

1 137. A method as in claim 136, further comprising using  
2 said computer file to control a controllable laser, to form an  
3 effect on a material.

1 138. A method of processing a garment, comprising:  
2 obtaining a first garment which has a desired look to be  
3 replicated;  
4 determining color levels of different areas of a plurality  
5 of different areas of said first garment;  
6 determining, from said color levels, an amount of effective  
7 applied energy of laser energy which will need to be applied to  
8 said each of said area to replicate said color level; and  
9 forming a computer file which has a plurality of area  
10 representations, each area representation associated with a  
11 power representation representing said amount of laser power  
12 which needs to be applied to each of said areas to replicate  
13 said different areas of said first garment.



1 139. A method as in claim 138 further comprising using said  
2 computer file to control a laser to mark a second garment in a  
3 way that replicates a pattern of the colors on the first  
4 garment.

1 140. A method as in claim 138 wherein said laser marks said  
2 second garment by scribing a plurality of lines on said second  
3 garment using said computer file.

1 141. An apparatus as in claim 140 wherein at least a  
2 plurality of said lines define an effective applied energy which  
3 varies within each of a plurality of single scanned lines.

1 142. A method as in claim 138 further comprising storing  
2 information in a look up table, and using said information to  
3 determine said effective applied energy for each of said areas.

1 143. A method as in claim 138 further comprising displaying  
2 a graphical image indicative of said computer file to a user and  
3 allowing said user to edit said graphical image to thereby edit  
4 said computer file.

1 144. A method, comprising:  
2 defining an image of a whisker part which represents an  
3 image of a color change to a material caused by creasing of the  
4 material; and  
5 forming a computer file which indicates said whisker part,  
6 and which which represents at least a plurality of areas, and  
7 laser information for said areas, said laser information for  
8 said areas being information which will cause said laser to form  
9 a specified color change of material in said areas.

1 145. A method as in claim 144, further comprising applying  
2 said computer file to a laser to simulate the look of said  
3 whisker part on the material.

1 146. A method as in claim 144 wherein said whisker part  
2 comprises a plurality of lines that represent the creases, each  
3 of the lines are between 1/8th of an inch and 2 inches in width  
4 and between one and ten inches in length.

1        147. A method as in claim 144 wherein each of the lines is  
2 a different color in the center then along the top, bottom and  
3 towards its edges.

1        148. A method comprising:  
2        defining a pattern to be formed on a textile material,  
3 which pattern represents different degrees of abrasion of said  
4 textile material at different locations, and which represents at  
5 least first areas which have no abrasion, and producing a  
6 computer readable file indicative of said pattern; and  
7        controlling a laser to form said pattern by first  
8 controlling said laser according to said file to produce an  
9 effective output power in said first areas which is greater than  
10 zero, but is less than a threshold beyond which a visible change  
11 will be made to said textile material, and to increase the  
12 effective output power at a boundary between said first areas,  
13 and other areas outside said first areas.

1 149. A method comprising:  
2 defining a pattern to be formed on a textile material,  
3 which pattern represents a plurality of sections, each section  
4 having a separately controllable amount of degree of change,  
5 said different degrees of change including at least a plurality  
6 of different levels of change;  
7 randomizing a precise point at which the degree of change  
8 actually is bounded between two adjacent levels; and  
9 forming a computer-readable file indicating said pattern  
10 and information about said degree of change, including the  
11 randomized boundary.

1 150. A method as in claim 149, wherein said degree of  
2 change information is information about an effective applied  
3 power level for a laser, and said file includes said information  
4 associated with location information.

1 151. A method as in claim 150, further comprising using a  
2 laser to apply said effective applied power levels at specified  
3 locations represented by said location information.

1        152. A method comprising:  
2        defining a pattern to be formed on a textile material,  
3        which pattern has different colors representing different  
4        degrees of change of said textile material at different  
5        locations, said different degrees of change including at least a  
6        plurality of different levels of change, each different level of  
7        change associated with an effective applied energy to be applied  
8        to said location;

9        defining a tool which allows a spray of incremental  
10       intensity onto the pattern, by defining a droplet size and  
11       trajectory, determining a location that is hit by a droplet;  
12       adjusting a color level of said location based on said hit so  
13       that said effective applied energy is adjusted by said hitting.

1       153. A method as in claim 152, wherein said colors are one  
2       of full colors or gray scales.

1       154. A method as in claim 152, wherein said locations are  
2       pixels.

1        155. A method as in claim 152, wherein said adjusting  
2 comprises incrementing a color level of said location to a next  
3 higher color level.

1        156. A method as in claim 152, wherein said effective  
2 applied energy is one of an energy density per unit time, a duty  
3 cycle of an output of a laser, a speed of movement of a laser, a  
4 distance of a laser or a number of passes of a laser.

1        157. A method as in claim 152, wherein said adjusting  
2 comprises incrementing a color level of said location to a next  
3 lower color level.

1        158. A method of providing a variable effect to a material,  
2 comprising:

3        changing an effective applied power from a laser to a  
4 material by making multiple passes of laser scans along specific  
5 segments of the pattern, each of said passes being carried out  
6 at constant power, speed and laser distance, but the combination  
7 of said multiple scans providing a varied effective applied  
8 power at said material.

1        159. A method as in claim 158, wherein said changing  
2 comprises defining a file having different levels of effective  
3 applied energy, and using said file to control a number of said  
4 passes which are carried out in each of a plurality of areas.

1        160. A method as in claim 159, wherein said areas are  
2 pixels.

1        161. A method as in claim 2, wherein said effective  
2 applied energy is one of an energy density per unit time, a duty  
3 cycle of an output of a laser, a speed of movement of a laser,  
4 or a distance of a laser.

1        162. A method as in claim 41, wherein said effective  
2 applied energy is one of an energy density per unit time, power  
3 level of a laser, a duty cycle of an output of a laser, a speed  
4 of movement of a laser, or a distance of a laser.

1        163. A method as in claim 93, wherein said effective  
2 applied energy is one of an energy density per unit time, power  
3 level of a laser, a duty cycle of an output of a laser, a speed  
4 of movement of a laser, or a distance of a laser.

1        164. A method as in claim 107, wherein said effective  
2 applied energy is one of an energy density per unit time, power  
3 level of a laser, a duty cycle of an output of a laser, a speed  
4 of movement of a laser, or a distance of a laser.

1        165. A method as in claim 150, wherein said effective  
2 applied energy is one of an energy density per unit time, power  
3 level of a laser, a duty cycle of an output of a laser, a speed  
4 of movement of a laser, or a distance of a laser.

1        166. An apparatus as in claim 59, wherein said effective  
2 applied energy is one of an energy density per unit time, power  
3 level of a laser, a duty cycle of an output of a laser, a speed  
4 of movement of a laser, or a distance of a laser.

1        167. An apparatus as in claim 82, wherein said effective  
2 applied energy is one of an energy density per unit time, power  
3 level of a laser, a duty cycle of an output of a laser, a speed  
4 of movement of a laser, or a distance of a laser.



1        168. A file format, comprising:  
2        a representation of a matrix of values, each value  
3        representing an amount of effective applied power to be applied  
4        to each area defined by each element of the matrix.

1        169. A format as in claim 168, wherein each element of  
2        said matrix is bit-mapped.

1        170. A format as in claim 168, wherein each value  
2        represents at least one of power level, duty cycle and or energy  
3        density per unit time for each of said areas.

1        171. A format as in claim 168, wherein each said area is a  
2        pixel.

1        172. A format as in claim 168, wherein said format also  
2        includes a value from which a direction of scanning by a laser  
3        should be carried out.

1 173. A file format, comprising:  
2 a representation of a matrix of values, each value  
3 representing an amount of power to be applied by a laser to each  
4 area defined by each element of the matrix; and  
5 a control value for said laser, indicating a direction of  
6 laser scanning.

1 174. A format as in claim 173, wherein said direction is  
2 one of horizontal or vertical scanning.

1 175. A method comprising:  
2 authoring a special image intended for use in changing the  
3 color of textile fabric, which has differently colored areas  
4 representing different levels of change of color to said textile  
5 fabric; and  
6 using said image to form a file that controls a laser to  
7 carry out said changing of color of said textile fabric.

1 176. A method as in claim 175, wherein said file includes  
2 levels of effective applied energy associated with said levels  
3 of change of color.

1 177. A method as in claim 176, wherein said effective  
2 applied energy is one of an energy density per unit time, power  
3 level of a laser, a duty cycle of an output of a laser, a speed  
4 of movement of a laser, or a distance of a laser.

1 178. A method as in claim 175, wherein said file includes  
2 a separate effective applied energy value for each pixel of the  
3 image.

1 179. A file format, comprising:  
2 a matrix of values, each value associated with an area and  
3 having a value which indicates an amount of lasing to be carried  
4 out by a laser, which matrix of values collectively forms  
5 information which can be used to use said laser to form a  
6 whisker on a material, said whisker representing a color change  
7 to a material caused by creasing of the material.

Abstract

Techniques of duty cycle and other power type modulation of  
a laser to enable new formation of new designs on textile  
material.


5


8-16-00tb3.doc

001060" J.66E.560

10

FIG 1







Operating Parameters		Power Profile	
Speed in inches per second	Layer scale factor in inches	W	H
15.15	1.0	102	102
Pattern Scale Factor		2	100
X	Y	3	102
1	1	100	100
Pattern Dimension on Laser		5	100
X	Y	7	100
37	32.1	100	100
Drawing Direction		13	100
G Horizontal	G Vertical	15	100
Draw Color Change		17	100
G Random	G Deterministic	19	100
Boundary Length	100 to 1000	21	100
100 to 1000		23	100
Random Number Seed	15.15	25	100
Est Pattern File	Save Current File	27	100
Save Pattern File	Change Selection	29	100
Pattern	Est	31	100
Pattern Display		33	100
G Color		35	100
G Grayshade		37	100
Reverse		39	100






FIG 14


1

```

P>view Display
P>C color
P>G grayscale
P>R reverse

```

15/11

[illegible]

Pattern File [C:\Program Files\Power Mod\Pattern File]

Operating Parameters

Speed in inches per second [100] Layer scale factor [100] units per inch [100]

Pattern Scale Factors

X [1] Y [1]

Pattern Dimension on Layers

X [5.9] Y [5.9]

Drawing Direction

☒ Horizontal ☐ Vertical

Draw Color Change

☐ Random ☐ Deterministic

Boundary Length

☐ 0 ☒ other [100]

Random Number Seed

[1000]


Pattern Display

☐ Color ☐ Grayscale ☐ Reverse

Power Profile

Power	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Power	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100

F166




09653997-090100

西醫

1

<b>Operating Parameters</b> Speed in inches per second _____ Lines per inch _____ Pattern Scale Factor _____ Pattern Dimension on Laser _____ X _____ Y _____ 91 91	
<b>Drawing Direction</b> <input type="checkbox"/> Horizontal <input type="checkbox"/> Vertical <b>Draw Color Change</b> <input type="checkbox"/> Random <input type="checkbox"/> Deterministic <b>Boundary</b> Length _____ Minimum Boundary _____ Random Number Seed _____ 13776	
<b>Exit Pattern File</b> Save Pattern File _____ Change Location _____ Exit	<b>Save Control File</b> Save Control File _____ Change Location _____ Exit

4



F-16 7

**Abstract**

Patient, F-30

## Power Profile

**PER RECORD**

12615

1-800-235-5888

3

**RESEARCH**

101

## Disorders

100

10

**Update**

**P. Mink**

1

## Expatriation

Save Points

1995


4

62

—

•


•

$$\frac{1}{\infty}$$


---

Percept Profile	
1	100
2	100
3	100
4	100
5	100
6	100
7	100
8	100
9	100
10	100
11	100
12	100
13	100
14	100
15	100
16	100
17	100
18	100
19	100
20	100
21	100
22	100
23	100
24	100
25	100
26	100
27	100
28	100
29	100
30	100
31	100
32	100
33	100
34	100
35	100
36	100
37	100
38	100
39	100
40	100
41	100
42	100
43	100
44	100
45	100
46	100
47	100
48	100
49	100
50	100
51	100
52	100
53	100
54	100
55	100
56	100
57	100
58	100
59	100
60	100
61	100
62	100
63	100
64	100
65	100
66	100
67	100
68	100
69	100
70	100
71	100
72	100
73	100
74	100
75	100
76	100
77	100
78	100
79	100
80	100
81	100
82	100
83	100
84	100
85	100
86	100
87	100
88	100
89	100
90	100
91	100
92	100
93	100
94	100
95	100
96	100
97	100
98	100
99	100
100	100


617



**Pattern: Files** [C:\inetpub\wwwroot\aspnet\aspnet\_client\aspnet\_client\_2.0.50727.0\aspnet\_client\_2.0.50727.0\Global.asax]

Operating Parameters		Power Profile	
Speed in meters per second	Layer scale factor	Raw	103
	in units per inch	lay	105
28.125	62	1	106
File Name: C:\ProgramData\...		2	107
Pattern Scale Factor:		3	108
X	Y	4	109
1	1	5	110
Pattern Dimension on Laser		6	111
X	Y	7	112
50	210	8	113
Drawing Direction		9	114
<input type="radio"/> Horizontal	<input type="radio"/> Vertical	10	115
Data Color Change		11	116
<input type="radio"/> Random	<input type="radio"/> Deterministic	12	117
Boundary Length		13	118
<input type="radio"/> No cutter	<input checked="" type="radio"/>	14	119
Random Number Seed		15	120
13776		16	121
Edit Pattern File		17	122
<input type="radio"/> Save Pattern File	<input type="radio"/> Change/Verify	18	123
Pattern Display		19	124
<input type="radio"/> Color	<input type="radio"/> Grayscale	20	125
<input type="radio"/> Reverse		21	126

FIG 10







Pattern File [C:\Users\user\Documents\Pattern1.dat]

Operating Parameters  
Speed (inches per second) [100] Laser scale factor [1.0]

Pattern Scale Factor  
X [1.0] Y [1.0]

Pattern Dimension on Laser  
X [1.0] Y [1.0]

Drumming Direction  
☐ Horizontal ☐ Vertical

Draw Code Change  
☐ Random ☐ Deterministic

Boundary Length [0.0001] ☒ Use curve ☐ Use straight

☐ Minimum Boundary

Random Number Seed [12345]

File Pattern File Save Control File

Save Pattern File Change Version

Close Pattern File Exit

Pattern Display

☐ Color

☐ Grayscale

☐ Reverse

Power Profile

Buy [0.0]

Low [0.0]

2 [0.0]

3 [0.0]

4 [0.0]

5 [0.0]

6 [0.0]

7 [0.0]

8 [0.0]

9 [0.0]

10 [0.0]

11 [0.0]

12 [0.0]

13 [0.0]

14 [0.0]

15 [0.0]

16 [0.0]


17 [0.0]

18 [0.0]

19 [0.0]

20 [0.0]

F(612)





**COMBINED DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled MATERIAL SURFACE PROCESSING WITH A LASER THAT HAS A SCAN MODULATED EFFECTIVE POWER TO ACHIEVE MULTIPLE WORN LOOKS, the specification of which:

☒ is attached hereto.

☐ was filed on \_\_\_\_\_ as Application Serial No. \_\_\_\_\_ and was amended on \_\_\_\_\_.

☐ was described and claimed in PCT International Application No. \_\_\_\_\_ filed on \_\_\_\_\_ and as amended under PCT Article 19 on \_\_\_\_\_.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information I know to be material to patentability in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim the benefit under Title 35, United States Code, §119(e)(1) of any United States provisional application(s) listed below:

U.S. Serial No.	Filing Date	Status
60/157,904	October 5, 1999	Pending

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose all information I know to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56(a) which became available between the filing date of the prior application and the national or PCT international filing date of this application:

U.S. Serial No.	Filing Date	Status
-----------------	-------------	--------

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

Country	Application No.	Filing Date	Priority Claimed	
			<input type="checkbox"/> Yes	<input type="checkbox"/> No
			<input type="checkbox"/> Yes	<input type="checkbox"/> No

Attorney's Docket No.:  
Client's Ref. No.:

**Combined Declaration and Power of Attorney**

Page 2 of 2 Pages

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Scott C. Harris, Reg. No. 32,030

Address all telephone calls to SCOTT C. HARRIS at telephone number (619) 823-7778

Address all correspondence to SCOTT C. HARRIS at:

Customer No. 23844  
Scott C. Harris  
P.O. Box 927649  
San Diego, CA 92192

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patents issued thereon.

Full Name of Inventor: Clarence H Martin  
Inventor's Signature: Clarence H Martin Date: 8/30/00  
Residence Address: 290 Eastchester Court; Gahanna, Ohio 43230  
Citizenship: USA  
Post Office Address: 290 Eastchester Court; Gahanna, Ohio 43230

Full Name of Inventor: \_\_\_\_\_  
Inventor's Signature: \_\_\_\_\_ Date: \_\_\_\_\_  
Residence Address: \_\_\_\_\_  
Citizenship: \_\_\_\_\_  
Post Office Address: \_\_\_\_\_

Attorney's Docket No.: TB3/TL/SCH

**COMBINED DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled MATERIAL SURFACE PROCESSING WITH A LASER THAT HAS A SCAN MODULATED EFFECTIVE POWER TO ACHIEVE MULTIPLE WORN LOOKS, the specification of which:

☒ is attached hereto.

☐ was filed on \_\_\_\_\_ as Application Serial No. \_\_\_\_\_ and was amended on \_\_\_\_\_.

☐ was described and claimed in PCT International Application No. \_\_\_\_\_ filed on \_\_\_\_\_ and as amended under PCT Article 19 on \_\_\_\_\_.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information I know to be material to patentability in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim the benefit under Title 35, United States Code, §119(e)(1) of any United States provisional application(s) listed below:

<u>U.S. Serial No.</u>	<u>Filing Date</u>	<u>Status</u>
60/157,904	October 5, 1999	Pending

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose all information I know to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56(a) which became available between the filing date of the prior application and the national or PCT international filing date of this application:

<u>U.S. Serial No.</u>	<u>Filing Date</u>	<u>Status</u>
------------------------	--------------------	---------------

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

<u>Country</u>	<u>Application No.</u>	<u>Filing Date</u>	<u>Priority Claimed</u>
			<input type="checkbox"/> Yes <input type="checkbox"/> No
			<input type="checkbox"/> Yes <input type="checkbox"/> No

Attorney's Docket No.:  
Client's Ref. No.:

## Combined Declaration and Power of Attorney

Page 2 of 2 Pages

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Scott C Harris, Reg. No. 32,030

Address all telephone calls to SCOTT C. HARRIS at telephone number (619) 823-7778

Address all correspondence to SCOTT C. HARRIS at:

Customer No. 23844  
Scott C. Harris  
P.O. Box 927649  
San Diego, CA 92192

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patents issued thereon.

Full Name of Inventor: DARRELL J. COSTIN

Inventor's Signature: *Darrell J. Costin* Date: 8/18/00

Residence Address: 29261 NOTTINGHAM CT.

Citizenship: US WESTLAKE, OH 44145

Post Office Address: \_\_\_\_\_

Full Name of Inventor: \_\_\_\_\_

Inventor's Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Residence Address: \_\_\_\_\_

Citizenship: \_\_\_\_\_

Post Office Address: \_\_\_\_\_